

2535 Rose Parkway
Sikeston, MO 63801
1-888-669-0003

Construction Trailer Specialists, Inc.

Rock Master: Frameless



Frameless Half Round End Dump

Specifications:

LENGTH:	32 FT.
BODY:	1/4" HARDOX 450 (175 KSI, 450 BRINELL HARDNESS)
NOSE & GATE:	3/16" HARDOX 450 (175 KSI, 450 BRINELL HARDNESS)
TOP RAIL:	3 1/2" X 5 1/2" X 1/4" 80,000 PSI ROLL FORMED
LONGITUDINAL:	8" X 8" 1/4" HIGH STRENGTH STEEL
BODY BRACES:	1/4" HIGH STRENGTH STEEL INTERNALLY STIFFENED
DRAFT ARMS:	5" X 3" X 1/4" STEEL TUBES WITH DROP LEGS
HOIST:	8"-5 STAGE INVERTED TRUNION MOUNT (CUSTOM HOIST)
SUSPENSION:	50,000 LB. SINGLE POINT SUSPENSION
AXLES:	ROCKWELL 25,000 LB., HUB PILOTED
RIMS:	EIGHT 24.5 X 8.25 10 HOLE DISC
TIRES:	11R X 24.5 RADIALS ON STEEL WHEELS
TAILGATE:	AIR OPERATED HIGH LIFT GIVES 87" OF CLEARANCE. BRACING CONSISTS OF 5 3/4" X 3 3/4" X 3/16" HIGH STRENGTH STEEL. MUD FLAPS INTEGRATED - "OVER THE CENTER" LOCKS.
LADDERS:	FRONT AND REAR
FENDERS:	REAR BOLTED ON
WIRE HARNESS:	CUSTOM FIT AND FULLY SEALED (GROTE)
LIGHTS:	ICC AND DOT APPROVED GROTE ULTRA BLUE SEAL LIGHTING SYSTEM
FINISH:	TRAILER IS SANDBLASTED, PRIMED, AND THEN PAINTED WITH CARBOLINE WHITE PAINT. GROTE REFLECTIVE IS APPLIED PER DOT REGULATIONS.
OPTIONS:	QUARTER FRAME, TRI-AXLE QUARTER FRAME, CRAMARO SLIDE & GO OR CRAMARO FLIP & GO (ELECTRIC OR MANUAL OPERATION, AIR RIDE QUATER FRAME, DUNLOP SP-160 11R X 22.5 TIRES, ALUMINUM WHEELS