

**EQUIPMENT
TRAILERS**



The TEREX Value Proposition

TEREX Corporation is a diversified global manufacturer of a broad range of equipment for the construction, quarrying, recycling, surface mining, shipping, transportation, refining, utility and maintenance industries. TEREX is dedicated to the manufacturing and marketing of high-quality capital equipment designed to improve our customers' productivity and return on invested capital. In addition to offering quality products at an affordable price, TEREX offers many value-added benefits through its sales/marketing, finance, parts and service organizations.

TEREX, the third largest construction and mining equipment manufacturer in the world, has over 15,000 team members worldwide and manufacturing in over 47 facilities in North America, South America, Europe, Asia and Australia. The TEREX name is backed by hundreds of years of experience from over 50 respected brands that make up the TEREX family.

TEREX Load King offers a broad range of hauling, loading and dumping equipment for the construction and transportation industries. Our products include:

- Detachable Gooseneck Trailers
- Folding Gooseneck Trailers
- Rigid Gooseneck Trailers
- Bottom Dump Trailers

Our products deliver the right combination of capabilities and value that can help assure desired return on invested capital. And the TEREX commitment to provide the best product value possible includes readily available and responsive distributor and factory product support resources that keep TEREX products operating productively and profitably.

FINANCING

TEREX has been successful at delivering the right equipment at the right price. Through TEREX Financial Services (TFS), we assist our customers with managing their financial goals while meeting their equipment needs. TFS offers a variety of financing solutions customizable to match our customer's needs.

SUPPORT

TEREX Load King is dedicated to offering superior product support through our parts, service and sales teams to support our dealer network and customers. Our team members work together to ensure up-time for customers, while always looking for new and innovative ways to get the job done.

TABLE OF CONTENTS

| | |
|--|-------|
| Signature Series Detachable Goosenecks | 4-5 |
| Specialty Series Detachable Goosenecks | 6-7 |
| DD Series Detachable Goosenecks | 8-9 |
| Folding Goosenecks | 10-11 |
| Rigid Goosenecks | 12-13 |
| Bottom Dumps | 14-15 |

**SIGNATURE SERIES
DETACHABLE GOOSENECK
TRAILERS**



Loaded With Value

- TEREX Load King trailers are engineered for strength, durability and safety.
- Dependable, cost-effective trailers.
- Low-profile scraper design gooseneck allows loaded weight to transfer forward for maximum customer capacity.
- Wide, self-aligning trough facilitates easy gooseneck attachment to the trailer.
- Four-position gooseneck ratchet allows multiple ride heights.
- Full-depth, removable folding outrigger brackets increase versatility with a wide-load option.
- TEREX Load King's exclusive use of knotless Apitong hardwood decking ensures long life.
- High quality air ride suspension system with height control offers smooth, solid transport.
- Rugged, heavy-duty construction provides long-haul durability.

SIGNATURE SERIES

| | Net Capacity Full Deck | Net Capacity Concentrated | Load Concentration @ 60 mph (96.5 kph) | Estimated Weight | Gooseneck Length | Swing Clearance | Platform Length | Platform Width |
|---------------------|------------------------------|---------------------------|--|-----------------------|---------------------|----------------------------------|-----------------|-----------------|
| 352SS | NA | 70,000 lbs (31,752 kg) | 12 ft (3.66 m) | 14,500 lbs (6,577 kg) | 10 ft 9 in (3.28 m) | 84 in (2.13 m) | 24 ft (7.32 m) | 102 in (2.59 m) |
| 553SS | 110,000 lbs (49,895 kg) | 100,000 lbs (45,359 kg) | 16 ft (4.88 m) | 17,600 lbs (7,983 kg) | 10 ft 9 in (3.28 m) | 84 in (2.13 m) | 24 ft (7.32 m) | 102 in (2.59 m) |
| 553/4SS | 110,000 lbs (49,895 kg) | 100,000 lbs (45,359 kg) | 16 ft (4.88 m) | 18,600 lbs (8,437 kg) | 12 ft (3.66 m) | 98 in (2.49 m) | 24 ft (7.32 m) | 102 in (2.59 m) |
| 503/554SS SF | 110,000 lbs w/SF (49,895 kg) | 100,000 lbs (45,359 kg) | 12 ft (3.66 m) | 20,200 lbs (9,163 kg) | 13 ft 3 in (4.04 m) | 92 in / 114 in (2.34 m / 2.90 m) | 24 ft (7.32 m) | 102 in (2.59 m) |

SIGNATURE SERIES DETACHABLE GOOSENECK TRAILERS



Heavy-Duty Solutions

- TEREX Load King trailers are engineered for strength, durability and safety.
- Ideal for transporting variably shaped products such as heavy scrapers, cranes and ships.
- Low deck height helps ensure loaded trailer meets required low clearance standards.
- Low-profile gooseneck design allows forward loading of scraper equipment, which maximizes weight distribution for extended transport on DDC, BT and MB models.
- The Beavertail (BT) model offers user-friendly rear loading capability for maximum productivity.
- Simplified and quick loading courtesy of the TDPS taper deck design that has an 11-degree loading angle.
- The TDPS provides a smooth transition from extended deck to subframe with a 17-degree loading angle — great for low powered equipment.
- Compliance with weight restrictions is simplified utilizing the MB model single point suspension that balances weight distribution across the axles.

SPECIALTY SERIES

| | Net Capacity Full Deck | Load Concentration @ 60 mph (96.5 kph) | Estimated Weight | Gooseneck Length | Swing Clearance (2 position gooseneck) | Platform Length | Platform Width (Standard) | Loaded Deck Height | Loaded Ground Clearance |
|------------------|---|---|---------------------------|------------------------|---|--------------------|------------------------------|-----------------------|----------------------------|
| 403DDC | 8,000 lbs (36,287 kg) | 10 ft (3.05 m) | 20,900 lbs (9,480 kg) | 12 ft 6 in (3.81 m) | 85 in / 107 in (2.16 m / 2.72 m) | 24 ft (7.32 m) | 120 in (3.05 m) | 18 in (46 cm) | 6 in (15 cm) |
| 503BT | 100,000 lbs (45,359 kg) | 12 ft (3.66 m) | 20,900 lbs (9,480 kg) | 12 ft 9 in (3.89 m) | 86 in / 108 in (2.18 m / 2.74 m) | 23 ft (7.01 m) | 102 in (2.59 m) | 24 in (61 cm) | 8 in (20 cm) |
| 352TDPS | 70,000 lbs (31,751 kg) | 10 ft (3.05 m) | 16,800 lbs (7,620 kg) | 10 ft 9 in (3.28 m) | 84 in (2.13 m) | 24 ft (7.32 m) | 102 in (2.59 m) | 24 in (61 cm) | 8 in (20 cm) |
| 503TDPS | 100,000 lbs (45,359 kg) | 12 ft (3.66 m) | 22,300 lbs (10,115 kg) | 12 ft 9 in (3.89 m) | 86 in / 108 in (2.18 m / 2.74 m) | 24 ft (7.32 m) | 102 in (2.59 m) | 24 in (61 cm) | 8 in (20 cm) |
| 503/554MB | 100,000 lbs (45,359 kg) 110,000 lbs w/MB (49,895 kg) | 12 ft (3.66 m) | 25,800 lbs (11,702 kg) | 13 ft 3 in (4.04 m) | 92 in / 114 in (2.34 m / 2.90 m) | 23 ft (7.01 m) | 102 in (2.59 m) | 24 in (61 cm) | 8 in (20 cm) |

**DD SERIES
DETACHABLE GOOSENECK
TRAILERS**



Hard-Working Heavy Haulers

- TEREX Load King trailers are engineered for strength, durability and safety.
- Special orders are not required for the TEREX Load King specialized large carriers. The DD models are pre-engineered and ready to go, dramatically reducing lead times.
- Meet industry standard weight requirements and maintain a consistent ride height with TEREX Load King's positive mechanical weight equalization system.
- Innovative subframe design ensures accurate, equal weight distribution to all axles.
- Experience a smooth, comfortable ride with the air ride suspension system that comes standard on all the DD models.
- Rugged, heavy-duty construction for long-haul durability.
- TEREX Load King uses highly durable, knotless Apitong hardwood decking on all models.
- Durable, industrial-strength acrylic enamel finish protects against corrosion and the elements.

DD SERIES

| | Net Capacity Full Deck | Load Concentration @ 60 mph (96.5 kph) | Estimated Weight (Standard trailers) | Gooseneck Length | Flipover Gooseneck Extension (included in total gooseneck length) | Swing Clearance (2 position gooseneck & flipover) | Platform Length | Platform Width (Standard) |
|------------------|----------------------------|--|--------------------------------------|------------------------|---|--|-------------------|---------------------------|
| 503/655DD | 130,000 lbs (58,967 kg) | 12 ft (3.66 m) | 34,900 lbs (15,830 kg) | 19 ft 6 in (5.94 m) | 66 in (1.68 m) | 85 in / 109 in / 175 in (2.16 m / 2.77 m / 4.45 m) | 26 ft (7.92 m) | 102 in (2.59 m) |
| 503/705DD | 140,000 lbs (63,503 kg) | 12 ft (3.66 m) | 35,500 lbs (16,102 kg) | 19 ft 6 in (5.94 m) | 66 in (1.68 m) | 85 in / 109 in / 175 in (2.16 m / 2.77 m / 4.45 m) | 26 ft (7.92 m) | 102 in (2.59 m) |
| 503/755DD | 150,000 lbs (68,039 kg) | 12 ft (3.66 m) | 39,500 lbs (17,917 kg) | 22 ft 6 in (6.86 m) | 84 in (2.13 m) | 103 in / 127 in / 211 in (2.61 m / 3.23 m / 5.36 m) | 26 ft (7.92 m) | 102 in (2.59 m) |



Paving the Way to Productivity

- TEREX Load King trailers are engineered for strength, durability and safety.
- Low loading angle makes transporting of asphalt pavers a breeze.
- These extremely versatile TEREX Load King trailers can be used with almost any tractor or truck.
- Optional built-in railroad rails simplify loading of railroad equipment, making these TEREX Load King trailers an industry favorite.
- The easy-to-use DFMR mechanical folding gooseneck can be easily operated via a winch mounted on the transporting truck.
- The DFP model's 7-degree low loading angle with a self-contained power unit to simplify and speed loading.
- The DFM model's 7-degree low loading angle simplifies loading on this mechanical folding gooseneck trailer via a truck-mounted winch.
- Knotless Apitong hardwood decking provides long-lasting durability.
- Durable, industrial-strength acrylic enamel finish protects against corrosion and the elements.

FOLDING GOOSENECK SERIES

| | Net Capacity Full Deck | Load Concentration @ 60 mph (96.5 kph) | Estimated Weight | Gooseneck Length | Swing Clearance | Platform Length | Platform Width |
|------------------|----------------------------|---|---------------------------|------------------------|---|--------------------|--------------------|
| 403/4DFMR | 80,000 lbs (36,287 kg) | 16 ft (4.88 m) | 21,600 lbs (9,798 kg) | 9 ft 8 in (2.95 m) | 106 in (2.69 m) | 25 ft (7.62 m) | 102 in (2.59 m) |
| 503DFP | 100,000 lbs (45,359 kg) | 16 ft (4.88 m) | 22,700 lbs (10,297 kg) | 9 ft 8 in (2.95 m) | 106 in / 85 in (2.69 m / 2.16 m) | 24 ft (7.32 m) | 102 in (2.59 m) |
| 503/4DFP | 100,000 lbs (45,359 kg) | 10 ft (3.05 m) | 23,400 lbs (10,614 kg) | 9 ft 8 in (2.95 m) | 106 in / 85 in (2.69 m / 2.16 m) | 24 ft (7.32 m) | 102 in (2.59 m) |
| 503DFM | 100,000 lbs (45,359 kg) | 10 ft (3.05 m) | 20,800 lbs (9,435 kg) | 11 ft 2 in (3.40 m) | 124 in / 110 in / 86 in (3.15 m / 2.79 m / 2.18 m) | 22 ft (6.71 m) | 102 in (2.59 m) |



Extreme Efficiency

- TEREX Load King trailers are engineered for strength, durability and safety.
- Ideal rental industry solutions for quick and efficient loading of multiple pieces of equipment.
- The HFT model’s hydraulically powered folding ramp with self-locking flip tail provides 12 ft (3.66 m) of low incline, increasing productivity and simplifying loading/unloading.
- The low maintenance SA70 sliding axle trailer has a low 6.5-degree tilting deck angle — ideal for loading heavy equipment and for the towing industry.
- The HFT and SA models come standard with an air ride suspension system and ABS brakes for a smooth ride to cushion and protect payloads.
- The 252LR model is an economical option for rear loading with a 14-degree load angle — the perfect choice for small contractors.
- The cost-effective 352RPS offers a low 7-degree rear loading angle, 13-degree deck-to-gooseneck transition, and hydraulic rear ramps.
- All trailers come standard with top-of-the-line knotless, long-lasting Apitong hardwood decking.

RIGID GOOSENECK SERIES

| | Net Capacity Full Deck | Net Capacity Concentrated | Load Concentration @ 60 mph (96.5 kph) | Estimated Weight | Gooseneck Length | Swing Clearance | Platform Length | Platform Width |
|---------------|---------------------------|---------------------------|--|--------------------------|------------------------|-------------------|-------------------------|--------------------|
| HFT70 | 70,000 lbs (31,752 kg) | 50,000 lbs (22,680 kg) | 16 ft (4.88 m) | 14,600 lbs (6,623 kg) | 8 ft (2.44 m) | 86 in (2.18 m) | 28 ft 6 in (8.69 m) | 102 in (2.59 m) |
| SA70 | 70,000 lbs (31,752 kg) | 50,000 lbs (22,680 kg) | 10 ft (3.05 m) | 17,000 lbs (7,711 kg) | 9 ft 11 in (3.02 m) | 86 in (2.18 m) | 38 ft 1 in (11.61 m) | 102 in (2.59 m) |
| 252LR | 50,000 lbs (22,680 kg) | 40,000 lbs (18,144 kg) | 8 ft (2.44 m) | 12,000 lbs (5,443 kg) | 7 ft (2.13 m) | 86 in (2.18 m) | 20 ft (6.10 m) | 102 in (2.59 m) |
| 352RPS | NA | 70,000 lbs (31,752 kg) | 14 ft (4.27 m) | 17,200 lbs (7,802 kg) | 8 ft (2.44 m) | 86 in (2.18 m) | 29 ft (8.84 m) | 102 in (2.59 m) |



Packed With Productivity

- Originators of the design, TEREX Load King bottom dump trailers are engineered for strength, durability and safety.
- With a high value-to-cost ratio, these bottom dump trailers set the industry standard at an affordable price.
- Roll and fill or empty your load without ever stopping.
- Largest lower hopper opening in the industry for increased productivity on any job.
- Select gate control options for every application, from pinching off the load to all open for a quick drop.
- Hopper opening cylinders located inside gates for maximum protection.

BOTTOM DUMP SERIES

| | Rated Net Payload @ 60 mph (96.5 kph) | Struck Capacity | Estimated Weight | Overall Width | Upper Hopper Opening | Lower Hopper Opening |
|------------------|--|--------------------|--------------------------|--------------------|-------------------------------------|-------------------------------------|
| 2066-40-2 | 66,000 lbs (29,937 kg) | 20 yd ³ | 12,700 lbs (5,760 kg) | 102 in (2.59 m) | 90 in x 187 in (2.29 m x 4.75 m) | 64 in x 106 in (1.63 m x 2.69 m) |
| 2066-40-3 | 66,000 lbs (29,937 kg) | 20 yd ³ | 14,700 lbs (6,668 kg) | 102 in (2.59 m) | 90 in x 187 in (2.29 m x 4.75 m) | 64 in x 106 in (1.63 m x 2.69 m) |

TEREX Load King is a member of the TEREX group of companies, which manufactures over 700 products worldwide, including aerial work platforms, construction, mining, utilities and roadbuilding. Other TEREX products not included in this publication:

AERIAL WORK PLATFORMS

Articulating booms
Material lifts
Trailer-mounted booms
Portable aerial work platforms
Scissor lifts
Telescopic booms

CONSTRUCTION

Compactors
Concrete finishing systems
Detour safety lighting
Excavators
Generators
Light towers
Material handlers
Motor graders
Off-highway trucks
Power buggies
Power trowels
Scrapers
Site dumpers
Tandem asphalt rollers
Telehandlers
Tractor loader backhoes
Trailers
Wheel loaders

CRANES

All terrain cranes
Boom truck cranes
Container reach stackers
Lattice boom cranes
Lift and carry cranes
Rough terrain cranes
Telescopic truck cranes
Tower cranes
Truck mounted cranes

MATERIALS PROCESSING & MINING

All wheel drive rear dump trucks
Crushers
Crushing and recycling systems
Drills
Screens
Surface mining equipment
Surface mining trucks
Trommels
Washing systems

UTILITIES & ROADBUILDING

Aerial devices- utilities
Asphalt mixing plants
Asphalt pavers
Cable placers
Concrete mixers
Concrete pavers
Concrete production plants
Digger derricks
Pavement profilers
Reclaimers/stabilizers



TEREX | LOAD KING

TEREX Load King

701 East Rose Street
P.O. Box 427
Elk Point, SD 57025
USA

TOLL FREE 888-264-5522
PHONE 605-356-3301
FAX 605-356-3268
EMAIL sales@loadkingtrailers.com
WEB www.loadkingtrailers.com
www.terex.com

Effective date: October, 2005. For further information, please contact your local distributor or the TEREX sales office listed. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. TEREX makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of TEREX Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. "TEREX" is a Registered Trademark of TEREX Corporation in the USA and many other countries. Copyright ©2006 TEREX Corporation.